

Broadband Light Source (BLS-L-A)

The LiComm BLS-L-A series are an incoherent light source with flattened output spectrum for single-mode component test and subsystem characterization in L-band communication window. The BLS has high output power, which is ten thousand times stronger than a white light source, very wide wavelength range, and excellent stability. It is an ideal source to test the spectral characteristics of any DWDM applications passive components such as fiber Bragg gratings, MUX/DEMUX, isolator, filters, couplers etc..

The BLS-L-A series offer the significant reducing of measurement time and cost and it can improve the component quality and performance. The GUI program and RS232 communication are available to control and monitor of the BLS status.



Features

- ▶ High output power
- ▶ Stable spectral output power
- ▶ Wide wavelength range (L-band)
- ▶ Isolated output
- ▶ Communication by RS232
- ▶ Easy operating and compact
- ▶ Flattened output spectrum


Applications

- ▶ DWDM components spectral test
- ▶ Optical components test
- ▶ Optical fiber characterization
- ▶ System compliance test
- ▶ Optical measurement system
- ▶ Optical sensors


Optical Characteristics

Parameter	Symbol	Min	Typ	Max	Unit
Wavelength range (@-10dBm/nm)	λ	1565	-	1608	nm
Total output power	P _{OUT}	-	13	-	dBm
Output power stability ¹⁾	PS	-	-	0.02	dB
Spectral power stability ²⁾	SS	-	-	0.1	dB
Spectrum flatness ³⁾	SF	-	2	-	dB
Output isolation	ISO	30	-	-	dB

Note 1) @23°C ± 3°C, after 1 hour warming up
 2) @23°C ± 3°C, after 1 hour warming up
 3) @ Output :13dBm



Output Power Spectrum



Total Output Power Stability

Electrical & Environmental

Parameter	Typical value
Power supply voltage	AC 110 ~ 220 V
Interface	RS232
Operating temperature	10 ~ 40°C
Storage temperature	-40 ~ 85°C
Storage humidity	0 ~ 95% R.H
Power consumption	10 W

*Output power = 13dBm (@25°C)

Ordering Information

BLS - L - PXX₁A

XX₁ : Output Power

Mechanical Dimension

